

Projekt: pora nocna

Dane do obliczeń :

•ród³a punktowe

Nr	X[m]	Y[m]	z[m]	Pma	Symbol
=====					
1	383.4	431.4	0.3	73.3	SO
2	391.6	416.5	0.3	73.3	SO
3	398.8	402.6	0.3	73.3	SO
4	405.0	389.6	0.3	73.3	SO
5	413.2	378.6	0.3	73.3	SO
6	415.6	413.6	0.3	73.3	SO
7	422.3	398.7	0.3	73.3	SO
8	426.6	385.8	0.3	73.3	SO
9	422.8	377.6	0.3	73.3	SO
10	405.0	411.7	0.3	73.3	SO
11	485.2	366.6	0.5	75.8	WW
12	597.0	363.2	0.5	75.8	WW
13	447.8	436.6	0.5	75.8	WW
14	537.0	441.9	0.5	75.8	WW
15	464.2	437.4	12.0	93.0	US
16	469.1	425.6	10.0	87.0	S
17	475.0	414.0	7.0	97.0	CH
18	492.0	396.6	1.0	90.0	W
19	488.1	393.8	30.0	83.0	K
20	431.8	444.2	8.3	80.0	WD
21	440.5	448.7	8.3	80.0	WD
22	522.6	491.3	8.3	80.0	WD
23	526.8	481.5	8.3	80.0	WD
24	547.5	451.2	8.3	80.0	WD
25	555.0	436.1	8.3	80.0	WD
26	565.1	417.6	8.3	80.0	WD
27	575.8	395.8	8.3	80.0	WD
28	532.6	384.0	10.3	80.0	WD
29	525.9	379.3	10.3	80.0	WD
30	511.9	374.0	10.3	80.0	WD
31	500.7	368.9	10.3	80.0	WD
32	417.6	339.8	5.3	80.0	WD
33	427.1	345.1	5.3	80.0	WD
34	509.4	428.0	10.3	80.0	WD
35	513.0	419.9	10.3	80.0	WD
36	510.5	365.3	10.5	90.0	AS
37	401.3	429.7	8.5	75.0	CW
=====					

•ród³a typu hala produkcyjna :

WSPÓŁRZĘDNE WIERZCHOŁKÓW :

Nr	X1[m]	Y1[m]	X2[m]	Y2[m]	X3[m]	Y3[m]	X4[m]	Y4[m]	h0[m]	h[m]
=====										
1	470.6	447.0	487.3	455.7	518.6	395.2	501.4	386.6	0.0	16.0
2	509.5	412.2	521.4	418.6	530.5	401.4	518.3	395.4	0.0	12.0
3	487.4	455.7	500.4	430.2	512.2	436.3	498.5	461.6	0.0	16.0
=====										

POZIOMY HAŁASU i IZOLACYJNOŚĆ PRZEGRÓD

Nr	Źródło	A	63	125	250	500	1000	2000	4000	8000	wsp.odb.
1	sc.1 L wew	90.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1.0000
	R sc	32.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	
	sc.2 L wew	90.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1.0000
	R sc	32.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	
	sc.3 L wew	90.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1.0000
	R sc	32.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	
	sc.4 L wew	90.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1.0000
	R sc	32.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	
	dach L wew	90.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1.0000
	R d	32.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	

Nr	Źródło	A	63	125	250	500	1000	2000	4000	8000	wsp.odb.
2	sc.1 L wew	90.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1.0000
	R sc	32.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	
	sc.2 L wew	90.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1.0000
	R sc	32.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	
	sc.3 L wew	90.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1.0000
	R sc	32.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	
	sc.4 L wew	90.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1.0000
	R sc	32.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	
	dach L wew	90.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1.0000
	R d	32.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	

Nr	Źródło	A	63	125	250	500	1000	2000	4000	8000	wsp.odb.
3	sc.1 L wew	90.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1.0000
	R sc	32.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	
	sc.2 L wew	90.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1.0000
	R sc	32.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	
	sc.3 L wew	90.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1.0000
	R sc	32.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	
	sc.4 L wew	90.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1.0000
	R sc	32.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	
	dach L wew	90.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1.0000
	R d	32.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	

Ekrany akustyczne :

WSPÓŁRZĘDNE WIERZCHOŁKÓW :

Nr	X1[m]	Y1[m]	X2[m]	Y2[m]	X3[m]	Y3[m]	X4[m]	Y4[m]	h0[m]	h[m]
1	510.8	491.8	520.6	473.3	538.3	482.2	528.1	500.5	0.0	8.0
2	534.0	458.1	574.2	381.9	590.6	391.0	550.6	466.7	0.0	8.0
3	423.9	449.3	431.0	435.0	448.9	444.6	441.7	458.7	0.0	8.0
4	390.6	430.2	396.2	420.6	410.8	428.3	405.5	438.1	0.0	8.0
5	396.4	420.8	403.1	419.4	409.2	422.2	410.8	428.0	0.0	8.0
6	487.4	379.2	530.5	401.8	544.9	373.9	500.7	352.5	0.0	10.0
7	500.4	430.2	509.7	412.2	521.4	418.4	511.9	436.2	0.0	10.0
8	410.0	340.6	413.0	334.4	433.0	344.4	429.4	350.6	0.0	5.0
9	436.0	389.0	441.0	391.4	438.4	396.7	435.7	393.3	0.0	6.0
10	441.0	391.4	438.4	396.4	442.8	396.7	446.2	393.9	0.0	6.0
11	440.9	391.4	435.7	388.8	438.8	386.5	443.5	386.8	0.0	6.0

12 440.8 391.4 443.6 386.7 446.0 389.4 446.0 393.8 0.0 6.0

WSPÓŁCZYNNIKI ODBICIA DLA ŚCIAN

Nr	ściana 1	ściana 2	ściana 3	ściana 4	dach
1	1.0000	1.0000	1.0000	1.0000	1.0000
2	1.0000	1.0000	1.0000	1.0000	1.0000
3	1.0000	1.0000	1.0000	1.0000	1.0000
4	1.0000	1.0000	1.0000	1.0000	1.0000
5	1.0000	1.0000	1.0000	1.0000	1.0000
6	1.0000	1.0000	1.0000	1.0000	1.0000
7	1.0000	1.0000	1.0000	1.0000	1.0000
8	1.0000	1.0000	1.0000	1.0000	1.0000
9	1.0000	1.0000	1.0000	1.0000	1.0000
10	1.0000	1.0000	1.0000	1.0000	1.0000
11	1.0000	1.0000	1.0000	1.0000	1.0000
12	1.0000	1.0000	1.0000	1.0000	1.0000

Punkty obserwacji

Nr	Symbol	X[m]	Y[m]	z[m]
1		240.4	160.6	4.0
2		271.6	122.0	4.0